Exterior Service Window

Exterior Service Window fits into rough wall opening and clamps onto wall. Adjustable extruded aluminum frame fits walls 5" to 8.5" thick. Window clamps in place with bolts positioned through back frame into threaded section of front frame. Glazing is sealed into the frame for weather tight installation. Stainless steel shelf has writing surface in front of built-in deal tray. Deal tray closure helps prevent drafts. Natural voice transmission is provided by the circular draft-free talk thru.

Specify frame finish:


Clear or dark bronze anodized aluminum

Construction:

Aluminum frame Stainless steel shelf

Bullet resistant glazing available:

1.25" acrylic Level I or 1.25" Lexgard Level III





	Overall Size of Unit	Wall Opening
Model	Width x Height	Width x Height
SWE 2436	24" x 36"	21.75" x 35"
SWE 3036	30″ x 36″	27.75" x 35"
SWE 3636	36″ x 36″	33.75″ x 35″
SWE 2442	24" x 42"	21.75″ x 41″
SWE 3042	30″ x 42″	27.75" x 41"
SWE 3642	36" x 42"	33.75" x 41"


Exterior Service Window with Multi-Lites

Exterior Service Window with Multi-Lites has adjustable aluminum clamp-on frame to fit walls 5" to 8.25" thick. Mullions divide window into two or more lites. Glazing is sealed into frame for weather tight installation. Draft-free circular talk thrus allow natural voice communication. Stainless steel shelf has recessed deal trays with closures.

Construction:

Aluminum frame Stainless steel shelf

Bullet resistant glazing available: 1.25" acrylic Level I or 1.25" Lexgard Level III





	Overall Size of Unit	Wall Opening
Model	Width x Height	Width x Height
SWE-ML 7236	72" x 36"	69.75" x 35"
SWE-ML 8436	84" x 36"	81.75″ x 35″
SWE-ML 9636	96" x 36"	93.75" x 35"